



NEW FALCON!
Graco's
newest pump
outperforms the
competition—
UP TO 33%!

**Falcon Oil and
Grease Pumps:
Dollar for dollar
and stroke for
stroke, few pumps
can match the
Falcon's
performance in
dispensing
medium-volume
lubricants.**

**Fast-Ball 1:1:
Redesigned to
perform optimally
at lower air supply
pressures**

Falcon™ Pumps

Oil and Grease Lubrication Pumps

3:1 Falcon

- **The Falcon 3:1 Ratio Oil and 50:1 Ratio Grease Lubrication Pumps**

Graco's Falcon pumps deliver the power and dependability you've come to expect from the leader in lubrication equipment. Even if dispensing oil and grease is only part of what you do, to accomplish it efficiently you need quality equipment. Graco's pumps are powerful enough to handle most types of oil and grease, and they perform dependably under rough conditions.



50:1 Falcon



Fast-Ball



■ Fast-Ball® 1:1

The Fast-Ball pump is the ideal choice for the transfer and dispensing of light lubricants such as motor oil, hydraulic oil and ATF. The Fast-Ball is available in stubby length for wall mounting or with various tube lengths to fit containers from 5 to 275 gallons (20 to 1100 liters).


- Now designed to operate at lower air supply pressure
- Great for oil dispense consoles and oil bars
- In-line design with few moving parts for less pump wear
- Differential air motor ensures reliable pumping
- Double-acting pump provides smooth fluid flow

Falcon 3:1 and 50:1 Technical Specifications


	3:1	50:1
Maximum fluid working pressure	650 psi (45 bar, 4.5 MPa)	7500 psi (517 bar, 52 MPa)
Maximum air inlet pressure	150 psi (10 bar, 1.0 MPa)	150 psi (10 bar, 1.0 MPa)
Ratio	3:1	50:1
Pump cycles per volume	28 per gal (7.39 per liter)	.52 per lb. (.115 per kg)
Volume per pump cycle	0.037 gal (0.140 liter)	.0019 lb. (.008 kg)
Maximum recommended pump speed	115 cycles per minute	115 cycles per minute
Recommended pump speed for continuous operation	95 cycles per minute	.95 cycles per minute
Maximum delivery	4.3 gpm (16.3 liters/min) at 115 cycles/minute	.2.2 lb/min (1.0 kg/min) at 115 cycles/minute
Stroke length	3.25 in. (82.5 mm)	3.25 in. (82.5 mm)
Maximum pump operating temperature	130°F (54°C)	130°F (54°C)
Air inlet size	3/8 npt(f)	3/8 npt(f)
Fluid outlet size	1/2 npt(f)	1/4 npt(f)
Fluid inlet size	1 1/2 npt(f)	N/A
Wetted parts	aluminum; carbon steel; chrome alloy steel; urethane; Buna-N; acetal; ultra-high molecular weight	carbon steel; zinc plating; ductile iron; polyurethane; ultra-high molecular weight polyethylene; polyethylene
*Sound pressure level at 70 psi air and 30 cpm	72.99 dB(A)	72.99 dB(A)
Sound power level at 70 psi air and 30 cpm	85.88 dB(A)	85.88 dB(A)
*Sound pressure level at 150 psi air and maximum cycle rate	79.36 dB(A)	79.36 dB(A)
Sound power level at 70 psi air and maximum cycle rate	92.25 dB(A)	92.25 dB(A)
Instruction Manuals		
Falcon 3:1 Pump		309223
Falcon 3:1 Package		308382
Falcon 50:1 Pump		309224
Falcon 50:1 Package		308300

*Sound pressure levels measured per ISO Standard 9614-2.

*Sound power levels measured per ISO Standard 9614-2.



Falcon 3:1 Package
244087



Falcon 50:1 Package
244098

Falcon Ordering Information

Falcon 3:1 Pumps

Falcon 3:1 Pump, Universal	244047
Falcon 3:1 Pump, 16 gal (60 L) cover	244048
Falcon 3:1 Pump, 55 gal (205 L) bung	244049
Falcon 3:1 Pump, 55 gal (205 L) cover	244050
Falcon 3:1 Pump, 275 gal (1100 L) bung	244051

Falcon 3:1 Packages

Falcon 3:1 Package, Universal, w/hose/fitting kit, and air reg kit	244085
Falcon 3:1 Package, 16 gal (60L), w/cover, hose/fitting kit, and air reg kit	244086
Falcon 3:1 Package, 55 gal (205 L), w/bung adapter, hose/fitting kit, and air reg kit	244087
Falcon 3:1 Package, 55 gal (205 L), w/cover, hose/fitting kit, and air reg kit	244088
Falcon 3:1 Package, 275 gal (1100 L), w/bung adapter, hose/fitting kit, and air reg kit	244089
Falcon 3:1 Package, bulk oil supply, w/pump, air reg, bung adapter, 350 Series reel, and EM5 meter	244090
Falcon 3:1 Package, bulk oil supply, w/pump, air reg, bung adapter, 250 Series reel, and EM5 meter	244091
Falcon 3:1 Package, bulk oil supply, w/pump, air reg, bung adapter, 250 Series reel, and EM5 meter (Canadian W&M)	244092
Falcon 3:1 Package, bulk oil supply, w/pump, air reg, bung adapter, 350 Series reel, and EM5 meter (Canadian W&M)	244093
Falcon 3:1 Package, 16 gal (60 L), w/cover, disp kit, and portable base	244094

Falcon 50:1 Pumps

Falcon 50:1 Pump, 35 lb (16 kg)	244044
Falcon 50:1 Pump, 120 lb (55 kg)	244045
Falcon 50:1 Pump, 400 lb (180 kg)	244046

Falcon 50:1 Packages

Falcon 50:1 Package, 120 lb (55 kg) w/disp kit, cover, and follower plate	244082
Falcon 50:1 Package, 120 lb (55 kg) w/elevator, and pump support	244083
Falcon 50:1 Package, 400 lb (180 kg), w/disp kit, cover, and follower plate	244084
Falcon 50:1 Package, 35-70 lb (16-32 kg), w/disp kit, cover, and follower plate	244095
Falcon 50:1 Package, 35-70 lb (16-32 kg), w/2-wheel truck, disp kit, pump support, and inductor plate	244096
Falcon 50:1 Package, 35-70 lb (16-32 kg), w/disp kit, cover, and pail	244097
Falcon 50:1 Package, 35-70 lb (16-32 kg), w/2-wheel truck, disp kit, cover, and pail	244098
Falcon 50:1 Package, 35-70 lb (16-32 kg), w/portable base, disp kit, cover, and pail	244099
Falcon 50:1 Package, 120 lb (55 kg), w/portable base, disp kit, cover, and follower plate	244100
Falcon 50:1 Package, 120 lb (55 kg), w/2-wheel truck, disp kit, cover, and follower plate	244101
Falcon 50:1 Package, 120 lb (55 kg), w/Heavy-duty 2-wheel truck, disp kit, cover, and follower plate	244102
Falcon 50:1 Package, 35 lb (16 kg), w/portable base, disp kit, 35 lb (16 kg) cover, 35 lb (16 kg) follower plate, and 70 lb (32 kg) pail	244103
Falcon 50:1 Package, 35 lb (16 kg), w/disp kit, 35 lb (16 kg) cover, and 35 lb (16 kg) follower plate	244104



Fast-Ball Ordering Information

Pumps

Fast-Ball 1:1 pump Universal222051
Fast-Ball 1:1 pump 55 gal (205 L) bung222103
Fast-Ball 1:1 pump 275 gal (1100 L) bung222104

Packages

Fast-Ball 1:1, non-metered disp. package, 55 gal (205 L)222602
Fast-Ball 1:1, metered disp. package, 55 gal (205 L)239702

Fast-Ball Technical Specifications

Maximum fluid pressure	180 psi (12.4 bar, 1.2 MPa)
Air pressure range	25 to 180 psi (1.7 to 12.4 bar, 0.17 to 1.2 MPa)
Air consumption	Approximately 1.5 cfm (0.042 m ³ /min) at 1 gpm (3.8 lpm) at 100 psi (0.7 MPa, 7 bar) air pressure

Sound data*

Sound pressure level74.9 dB(A)
Sound power level83.5 dB(A)
Effective piston area	1.48 sq. in. (9.55 sq. cm)
Maximum recommended fluid flow rate for continuous operation	2.5 gpm (9.5 lpm)
Maximum pump operating temperature	130°F (54°C)
Air inlet size1/4 npt(f)
Fluid outlet size3/4 npt(f)

Instruction Manuals

Fast-Ball 1:1 Pump	307906
Fast-Ball 1:1 Package	307637

*Sound measurements were taken at 100 psi air (7 bar, 0.7 MPa) inlet pressure at 40 cycles per minute per ISO Standard 3744.

All written and visual data contained in this document are based on the latest product information available at the time of publication. Graco reserves the right to make changes at any time without notice.

Sales/Distribution

Toll Free, North America
800-367-4023
612-623-6743
FAX 612-623-6580
www.graco.com

Graco Inc. is registered to I.S. EN ISO 9001

